

Stainless Steel Bolting Cloth



TYPE 316

Bolting Cloth is commonly used

for high capacity sifting where

increased through-put per screen is important.

APPROXIMATE APERTURE mm & microns	WIRE DIAMETER Ø mm	OPEN AREA %	IMPERIAL MESH
1.6mm	0.22	77	14
1.4	0.22	75	16
1.18	0.22	71	18
1.04	0.22	68	20
950 microns	0.22	66	22
850	0.22	63	24
780	0.2	63	26
710	0.2	61	28
680	0.165	65	30
630	0.165	63	32
580	0.165	61	34
540	0.165	59	36
500	0.165	57	38
475	0.16	56	40
460	0.14	59	42
44	0.14	57	44
410	0.14	56	46
390	0.14	54	48
375	0.14	53	50
350	0.14	51	52
320	0.114	55	58
310	0.114	53	60
300	0.114	52	62
280	0.10	54	66
260	0.09	54	72
250	0.09	53	74
240	0.09	52	76
220	0.09	50	80
210	0.09	50	84
200	0.09	48	88
180	0.09	45	94
150	0.065	47	120
130	0.06	47	135
105	0.05	47	165
90	0.04	46	200
75	0.04	43	220

AVAILABLE IN 1530mm WIDTH

OTHER APERTURES AVAILABLE UPON REQUEST